

Name **NEW YORK**
Number **KT101**

kinetura
By Tekna

General

Location	Indoor
Main Material	Phosphor Bronze
IP Class	IP20
Class	III
Bathroom zone	Not applicable
Voltage	24V DC
Power supply	Included 24V DC/65W
Cable length (m)	1,4m + 3,1m (power supply)
Dimensions (mm/ W-H-D)	Base: 220-220-180 Height: 1005mm
Mounting method	Stand-alone
Gross weight (kg)	6,8kg
Gross weight (kg)	4,5kg
Packaging (mm / W-H-D)	1098-300-293mm








Lamp

Light source	CCFL
Number of light sources	1
Power consumption	26W
Luminous flux	1360lm
Color temperature	2300K
CRI	80
Lifetime	50.000hrs
0% to 100%	35Sec

Electrical

Switch	Yes (Capacitive sensing)
Battery	No
Dimmable	Yes
Dimming range	<20% to 100%
Dimming method	Capacitive sensing
Supply Frequency	50Hz / 60Hz
Driver/Ballast Voltage	110-240 VAC/ 50-60 HZ
Rated Power	30W

Finishes

Interior finish		Brushed Bronze
		Lacquered Ghost White
Exterior finish		Acid Green
		Aged Bronze
		Brushed Bronze
		Lacquered Jet Black
		Lacquered Ghost White

